

Product Datasheet

2-port Gigabit Single-mode Dual Fiber Media Converter

(1110-SLX-F)



OVERVIEW

The 1110-SLX-F series is a gigabit fiber media converter. It has 1*10/100/1000Base-T port and 1*1000M uplink SFP fiber port, User can select different optical modules, such as multi-mode dual fiber, single-mode dual fiber, and single-mode single fiber. The media converter adopts the enterprise-class Taiwan Realtek company's carrier-grade chip solution, which has stable performance, good quality and high cost performance. It is suitable for optical fiber access application scenarios such as security monitoring, wireless coverage, intelligent transportation, and safe cities to form a cost-effective and stable communication network.

Unmanaged model, plug and play, no configuration, easy to use.

FEATURE

■ Gigabit photoelectric Ethernet conversion transmission

- ◇ Support gigabit RJ45 port and gigabit SFP fiber port combination, which enables users to flexibly build networking to meet the needs of various scenarios.
- ◇ Support non-blocking wire-speed forwarding.
- ◇ Support full-duplex based on IEEE802.3x and half-duplex based on Backpressure.

■ Easy to use and simple to maintain

- ◇ Compatible with IEEE802.3ab 1000Base-T, IEEE802.3z 1000Base-X network protocol, gigabit R45 port rate auto-negotiation
- ◇ Support full-duplex/half-duplex working mode with auto-negotiation function
- ◇ Automatic identification of twisted pair MDI/MDI-X cross lines and parallel lines
- ◇ Plug and play, no configuration required, centralized power supply and centralized connection management through 2U-14 slot rack
- ◇ LED working status indication for network diagnosis and fault checking, reducing maintenance workload.

■ Stable and reliable



- ◇ Low power consumption, No fan, galvanized steel casing.
- ◇ CCC, CE, FCC, RoHS.
- ◇ Comply with telecommunication network access requirements, and have the telecommunications equipment network access license of the MIIT.

TECHNICAL SPECIFICATION

Model	1110-MLX-F	1110-SLX-F	1110S-SLX-F-A/B
Interface Characteristics			
Interface	1* 10/100/1000Base-T RJ45 port (Data) 1*1000M uplink SFP fiber port (Data)		
Ethernet Port	10/100/1000Base-T auto-sensing, full/half duplex MDI/MDI-X self-adaption		
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP(≤100 meter) 100BASE-TX: Cat5 or later UTP(≤100 meter) 1000BASE-T: Cat5e or later UTP(≤100 meter)		
Optical Fiber Port	1.25Gbps, Multi-mode dual fiber LC port	1.25Gbps,Single-mode dual fiber LC port	1.25Gbps,Single-mode single fiber LC port
Optical Cable/Distance	Multi-mode: 850nm / 0-500m Single-mode: 1310nm / 0-40km, 1550nm/ 0-120km.		
Chip Parameter			
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T, IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T, IEEE802.3z 1000Base-X, IEEE802.3x		
Forwarding Mode	Store and forward(Full wire speed)		
Switching Capacity	2.0Gbps (Non-blocking)		
Forwarding Rate@64byte	3.0Mpps		
MAC	2K		
Buffer Memory	1M		
Jumbo Frame	1632byte		
LED Indicator	Power: PWR (Green), Data: L/A (Green), Half/full duplex: FDX (Green), Speed: 100/1000 (Green: 1000M@On, 1000M@Off)		
Power Supply			
Total PWR / Input	3.5W/ (5VDC)		


Voltage	
Power Consumption	Standby<1W, Full Load<4W
Physical Parameter	
Operation TEMP / Humidity	-20~+55°C, 5%~90% RH Non condensing
Storage TEMP / Humidity	-40~+85°C, 5%~95% RH Non condensing
Dimension (L*W*H)	94*70*27mm
Net /Gross Weight	<0.3kg / <0.5kg
Installation	Desktop, 2U-14 Rack-mounted
Certification & Warranty	
Lightning Protection	Lightning protection: 4KV 8/20us, Protection level: IP30
Certification	CCC, CE mark, commercial, CE/LVD EN60950, FCC Part 15 Class B, RoHS
Warranty	3 years, lifelong maintenance.

DIMENSION



A. 1*1.25G SFP fiber port
 B. 1*10/100/1000M RJ45 port
 C. DC5V power input port

APPLICATION



ORDERING INFORMATION

Model	Description
1110-MLX-F	Gigabit multi-mode dual fiber media converter with 1*10/100/1000M RJ45 port and 1*1.25G SFP fiber port. Total power is 4W, 850nm wavelength, default transmission distance 0-550m. External power supply: AC100-240V input.
1110-SLX-F	Gigabit single-mode dual fiber media converter with 1*10/100/1000M RJ45 port and 1*1.25G SFP fiber port. Total power is 4W, 1310nm wavelength, default transmission distance 0-20km. External power supply: AC100-240V input.
1110S-SLX-F-A	Gigabit single-mode single fiber media converter with 1*10/100/1000M RJ45 port and 1*1.25G SFP fiber port. Total power is 4W, 1310nm wavelength, default transmission distance 0-20km. External power supply: AC100-240V input.
1110S-SLX-F-B	Gigabit single-mode single fiber media converter with 1*10/100/1000M RJ45 port and 1*1.25G SFP fiber port. Total power is 4W, 1550nm wavelength, default transmission distance 0-20km. External power supply: AC100-240V input.
1110-MCX-O	Gigabit multi-mode dual fiber media converter with 1*10/100/1000M RJ45 port and 1*1.25G SC fiber port. Total power is 4W, 850nm wavelength, default transmission distance 0-550m. External power supply: AC100-240V input.
1110-SCX-O	Gigabit single-mode dual fiber media converter with 1*10/100/1000M RJ45 port and 1*1.25G SC fiber port. Total power is 4W, 1310nm wavelength, default transmission distance 0-20km. External power supply: AC100-240V input.
1110S-SCX-O-A	Gigabit single-mode single fiber media converter with 1*10/100/1000M RJ45 port and 1*1.25G SC fiber port. Total power is 4W, 1310nm

	wavelength, default transmission distance 0-20km. External power supply: AC100-240V input.
1110S-SCX-O-B	Gigabit single-mode single fiber media converter with 1*10/100/1000M RJ45 port and 1*1.25G SC fiber port. Total power is 4W, 1550nm wavelength, default transmission distance 0-20km. External power supply: AC100-240V input.
1110-MCX-K	Gigabit multi-mode dual fiber media converter with 1*10/100/1000M RJ45 port and 1*1.25G SC fiber port. Total power is 4W, 850nm wavelength, default transmission distance 0-550m. Support one-click switch LFP enable and store-forward / pass-through forwarding. External power supply: AC100-240V input.
1110-SCX-K	Gigabit single-mode dual fiber media converter with 1*10/100/1000M RJ45 port and 1*1.25G SC fiber port. Total power is 4W, 1310nm wavelength, default transmission distance 0-20km. Support one-click switch LFP enable and store-forward / pass-through forwarding. External power supply: AC100-240V input.
1110S-SCX-K-A	Gigabit single-mode single fiber media converter with 1*10/100/1000M RJ45 port and 1*1.25G SC fiber port. Total power is 4W, 1310nm wavelength, default transmission distance 0-20km. Support one-click switch LFP enable and store-forward / pass-through forwarding. External power supply: AC100-240V input.
1110S-SCX-K-B	Gigabit single-mode single fiber media converter with 1*10/100/1000M RJ45 port and 1*1.25G SC fiber port. Total power is 4W, 1550nm wavelength, default transmission distance 0-20km. Support one-click switch LFP enable and store-forward / pass-through forwarding. External power supply: AC100-240V input.

PACKING LIST

PACKING LIST	CONTENT	QTY	UNIT
	2-port gigabit single-mode dual fiber media converter	1	SET
	User Guide	1	PC
	Warranty Card	1	PC